

TAKAMAZ

2-Spindle 2-Turret Compound Machining CNC Lathe

XY-120 PLUS



**Evolved further as a perfect
TAKAMAZ turning machine**

Large Capacity for Number of Tools

- Main turret (12 stations) has a middle indexing capability, making it possible to mount tools on the 24-positions. Moreover, with the sub turret, the maximum number of tools becomes 36. This is an extensive number of tooling capable of cutting different types of different amount of workpieces at shorter idle time.

Innovative Short Cycle Time

- With the sub spindle for overlap cutting and main and sub spindle simultaneous cutting, the cycle time is significantly reduced.

Achieving Σ Loader Installation

- By designing the Y-axis at 30 degree, the TAKAMAZ compact type loader can be mounted. This is a new automation system innovation.

Machine Specifications

Item	Unit	Main-spindle	Sub-spindle
Capacity	Max. turning diameter	mm	φ170
	Max. turning length	mm	330
	Max. bar diameter	mm	φ42 (φ51)
	Chuck size	Inch	Collet/6
Spindle	Spindle nose	JIS	A2-5 (A2-6)
	Spindle bearing I.D.	mm	φ85 (φ100)
	Through-hole on spindle	mm	φ52 (φ61)
	Spindle speed	min ⁻¹	Max. 5,000 (Max. 4,000)
Tool post	Spindle indexing		Cs-axis
	Type		12-station turret, 24ST
	Tool shank	mm	□20
	Boring holder I.D.	mm	φ25
Motors	Max. stroke	mm	X:150 Z:330 Y:±35 X2:150 Z2(A):440
	Rapid traverse rate	m/min	X:18 Z:24 Y:±12 X2:18 Z2(A):18
	Spindle motor	kW	AC7.5/5.5 (AC11/7.5)
	Feed motor	kW	X:AC1.2 Z:AC1.4 Y:AC0.75 X2:AC0.75 Z2(A):AC1.2
Power tools	Coolant motor	kW	AC0.25×2
	Hydraulic motor	kW	AC1.5
	Tool storage capacity	pcs.	12
	Spindle speed	min ⁻¹	Max. 4,000
Capacity	Power tools motor	kW	AC3.7/2.2/1.5
	Drill	mm	φ13
	Endmill	mm	φ13
	Tap	mm	M8
Cs-axis	Rapid traverse rate	deg/min ⁻¹	21,600
Size	Spindle center height	mm	1,050
	L×W×H	mm	2,500×1,850×1,700
	Machine weight	kg	3,900
Total electric capacity		KVA	28(31)

():Option

Standard Accessories

- O.D. holder 2sets
- Boring holder 2sets
- Cut-off holder 1set
- Collet flange (Main, Sub) 1set ea.
- Sub-spindle (Hydraulic) 1set
- Main Spindle Cs-axis orientation 1set
- Sub Spindle Cs-axis orientation 1set
- Power tools drive unit 1set
- Coolant unit 1set
- Service tool kit 1set
- TAKAMAZ instruction manual 1set

Optional Accessories

- Power tools(Face/Side milling)
- Stroke adjusting cylinder
- Hydraulic chucks (Main:6,Sub:5)
- Collet chucks
- Sub-spindle parts ejector
- Sub turret
- Automatic door system
- Air blow unit
- No Sub-spindle spec
- Tailstock
- TAKAMAZ loader system
- Rear coolant unit
- Cycle end signal light (1-color/2-color/3-color)
- Chip conveyor(Right/Left)
(Floor type/Spiral type)
- Bar feeder system
- Parts catcher
- Out-conveyor
- Work set detector
- Cut-off check device
- Special color
- Others*

*For more information on attachments, consult our sales representative.

**TAKAMATSU MACHINERY CO., LTD.**

■ HEAD OFFICE & PLANT
1-8 ASAHI GAKKA HAKUSAN-CITY ISHIKAWA JAPAN. 924-8558 TEL +81-(0)76-274-1403 FAX +81-(0)76-274-8530

■ EUROPE OFFICE
INDUSTRIEGBIET, DIEPENBROICH 27 D-51491 OVERATH, GERMANY
TEL +49-(0)2206-866-150 FAX +49-(0)2206-865-123

TAKAMAZ TRADING (HANG ZHOU) CO., LTD.

120 SHINXIN NORTH ROAD, XIAOSHAN ECONOMY AND TECHNOLOGY DEVELOPMENT AREA,
HANGZHOU, ZHEJIANG PROVINCE, CHINA TEL +86-(0)571-8287-9709 FAX +86-(0)571-8286-5311

TAKAMATSU MACHINERY USA INC.

■ CHICAGO HEAD OFFICE
1320 LANDMEIER ROAD ELK GROVE VILLAGE, IL 60007 USA TEL +1-(0)847-981-8577 FAX +1-(0)847-981-8599

■ CINCINNATI OFFICE
5233 MUHLHAUSER ROAD, WEST CHESTER TOWNSHIP, OH 45011 USA TEL +1-(0)513-870-9777 FAX +1-(0)513-870-0325

TAKAMATSU MACHINERY (THAILAND) CO., LTD.

■ THAILAND HEAD OFFICE
88/17 MOO 19 BANGPLEE-DAMRU ROAD., BANGPLEEYAI, BANGPLEE, SAMUTPRAKARN 10540
TEL +66-(0)2-382-5372 FAX +66-(0)2-382-5373

TAKAMAZ MACHINERY EUROPE GmbH

■ EUROPEAN HEAD OFFICE
INDUSTRIEGBIET, DIEPENBROICH 27 D-51491 OVERATH, GERMANY
TEL +49-(0)2206-919-3960 FAX +49-(0)2206-865-123

<http://www.takamaz.co.jp/>

Controller Specifications

Item	TAKAMAZ&FANUC Oi-TD
Controlled axes	7 axes (X1, Z1, C1, Y, X2, Z2, C2)
Simultaneously controllable axes	Simultaneously 4 axes
Least input increment	0.001mm(X in diameter)
Least command increment	X: 0.0005mm Z, Y: 0.01mm
Auxiliary function	M3 digits
Spindle function	S4 digits
Tool function	T4 digits
Tape code	EIA(RS232C)/ISO(840)automatic recognition
Cutting feedrate	1~5,000mm/min
Command system	Incremental/Absolute
Linear interpolation	G01
Circular interpolation	G02, G03
Cutting feedrate override	0~150%
Rapid traverse override	F0, 100%
Program number	4 digits
Backlash compensation	0~9999 μm
Program memory capacity	1Mbyte (2,560m) (Dual systems total)
Tool offsets	128 sets(Dual systems total)
Registered programs	800 pcs.(Dual systems total)
Tool geometry/Wear offset	Standard
Canned cycle	G90, G92, G94
Radius designation on arc	Standard
Tool offset measurement input	Standard
Background editing	Standard
Direct drawing dimension programming	Standard
Custom macro	Standard
Additional custom macro common variables	#100~#199, #500~#999
Pattern data input	Standard
Nose R compensation	G40, G41, G42
Inch/Metric conversion	G20/G21
Programmable data input	G10
Run hour/Parts count display	Standard
Extended part program editing	Standard
Multiple repetitive cycle	G70~G76
Multiple repetitive cycle II	Pocket-shaped
Spindle synchronous control	Standard
Sub-spindle torque skip	Standard
Y-axis offset	Standard
Rigid tapping	For Power Tools only
Polar coordinate interpolation	Standard
Cylindrical interpolation	Standard
Canned drilling cycle	Standard
Constant surface speed control	G96, G97
Continuous thread cutting	G32
Variable lead thread cutting	G34
Thread cutting retract	Standard
Clock function	Standard
Help function	Standard
Alarm history display	50 pcs.
Self-diagnosis function	Standard
Self-diagnosis function	Up to 10 loops
Decimal point input	Standard
2nd reference point return	G30
Work coordinate system setting	G50, G54~G59
Stored stroke check 1	Standard
Stored stroke check 2,3	Standard
Input/Output interface	USB Flash Memory, Memory card, Ethernet
Alarm message	Standard
Graphic display	Standard
Conversational programming with graphic function	Standard
Abnormal load detection	Standard
Overlap Cutting Process	Standard
Manual handle trace	Standard
Automatic data backup	Max.3
Automatic screen deletion function	Standard
Spindle orientation	Standard
TAKAMAZ option functions	Work/Tool counter, Tool load monitor, Others
TAKAMAZ maintenance function	Standard
FANUC set of manuals	CD-ROM

Optional Controller Specifications

Input/Output interface	RS232C
Tool life management	
Multiple M codes in one block	Max.3
Dynamic graphic function*	
Helical interpolation	
Manual guide i*	
FANUC instruction manuals	Bound

*These cannot be used together.

●Distributed by:

Precautionary Remarks in connection with the Export Trade Control Ordinance
The export of this product is subject to an authorization from the government of the exporting country.
Check with the government agency for authorization.

The product shipped to you (the machine and accessory equipment) has been manufactured in accordance with the laws and standards that prevail in the relevant country or region. Consequently it cannot be exported, sold, or relocated, to a destination in a country with different laws or standards.

Specifications and accessories are subject to change without notice.
Standard specifications of the machine may differ according to destinations.



This brochure is made
from 100% recycled paper.